



MATERIAL SAFETY DATA SHEET

DATE PREPARED: March 12, 2004

Dynatex International urges each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or experts in ventilation, toxicology, and fire prevention, as necessary or appropriate to use and understand the data contained in this MSDS.

To promote safe handling, each customer or recipient should: (1) notify its employees, agents, contractors and others whom it knows or believes will use this material of the information in this MSDS and any other information regarding hazards or safety; (2) furnish this same information to each of its customers for the product; and (3) request customers to notify their employees, customers, and other users of the product of this information.

1. PRODUCT IDENTITY AND COMPANY CONTACT INFORMATION

Material Identity

Product Name: CONDUCTIVE WAFER GRIP ADHESIVE FILM (CWG)

General or Generic ID: EVA (Ethylene/Vinylacetate Copolymer)

Company

Dynatex International
5577 Skylane Blvd.
Santa Rosa, CA. 95403
707-542-4269

2. CHEMICAL COMPOSITION / INFORMATION ON INGREDIENTS

<u>Ingredients:</u>	<u>CAS Number</u>	<u>% (by weight)</u>
Proprietary Adhesive	N/A	N/A
Silver	7740-22-4	2.0 %
Automate Purple RS	Mixture*	< 0.3%

* See additional information on ingredients listed in the sections below.

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye:

May cause mild eye irritation.

Skin:

Solid product not expected to cause irritation. Molten material may cause thermal burns, dis-coloration, and may adhere to skin.

Ingestion:

Swallowing small amounts of this material may cause argyria (a permanent bluish-grey discoloration of the skin, conjunctiva and mucous membranes). Swallowing large amounts may be more harmful.

Inhalation:

May cause irritation, discomfort, pigmentation of nasal septum, mild bronchitis and argyria.

Symptoms of Exposure:

A permanent bluish-grey discoloration of the skin, conjunctiva and mucous membranes.

Target Organ effects:

No Data

Developmental Information:

No Data

Cancer Information:

Contains no materials known to the State of California (USA) to cause cancer and to cause adverse reproductive effects.

Other Health Effects:

No Data

Primary Route(s) of Exposure:

Inhalation, skin contact.

4. FIRST AID MEASURES

Eyes:

For contact with eyes, seek medical help immediately.

Skin:

For contact with molten material, immerse affected area immediately in clean, cold water. Leave adhesive in place and contact your physician.

Ingestion:

Seek medical help immediately.

Inhalation:

Exit polluted area as quickly as possible and proceed to a location where fresh air is readily available.

5. FIRE-FIGHTING MEASURES

Flash Point:

395°F (Cleveland Open Cup)

Explosive Limit:

N/A

Autoignition Temperature:

N/A

Hazardous Products of Combustion:

Combustion may form carbon dioxide and carbon monoxide.

Fire and Explosion Hazards:

No special fire hazards are known to be associated with this product.

Extinguishing Media:

Dry chemical, foam, carbon dioxide.

Fire Fighting Instructions:

Avoid using water on molten materials as this may cause splattering and spread of fire. Self-contained breathing apparatus and protective cloth should be worn in fighting fire involving chemicals.

6. ACCIDENTAL RELEASE MEASURES**Spill Procedure:**

Sweep up solid material. For molten material allow to solidify, then scrape, sweep up and place in a proper disposal container.

7. HANDLING AND STORAGE**Handling:**

Use gloves when handling solid material. For molten material take precautions against thermal burns.

Storage:

Store in a cool, dry place.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**Eye Protection:**

Chemical safety glasses should be worn.

Skin Protection:

Use gloves when handling solid material. For molten material be sure to wear appropriate OSHA approved safety equipment to prevent against thermal burns.

Respiratory Protection:

None should be needed, other than adequate ventilation.

Engineering Controls:

None for solid material. For molten material, good general room ventilation with at least twelve air changes per hour or a good exhaust ventilation system is suggested.

Exposure Guidelines:

Silver – PEL(OSHA): 0.01 mg/m³ Oral LD: >5 gm/kg (gpg)

Automate Purple RS contains the following components:

C.I. Solvent Blue 98 – No Data

C.I. Solvent Red 164 – No Data

Xylene (28.8%) – TLV (ACGIH): 100 PPM STEL(ACGIH): 150 PPM

PEL (OSHA): 100 PPM STEL (OSHA): 150 PPM

Ethyl Benzene (7.2%) – TLV (ACGIH): 100 PPM STEL(ACGIH): 150 PPM

PEL (OSHA): 100 PPM STEL (OSHA): 150 PPM

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: >350 °F

Softening Point: 208 °F

Vapor Pressure: No Data

Vapor Density: No Data

Specific Gravity: ~ 1.00

Percent Volatiles (by volume): No Data

Evaporation Rate: Negligible

Appearance: Purple

State: Solid

Odor: N/A

PH: N/A

Solubility in Water: Negligible

10. STABILITY AND REACTIVITY

Hazardous Polymerization:

Product will not undergo hazardous polymerization.

Hazardous Decomposition:

Combustion may produce carbon dioxide and carbon monoxide.

Chemical Stability:

Silver may react with acetylene or ammonia to form shock sensitive compounds.

Chemical Incompatibility:

Avoid oxidizing agents, acids and bases.

11. TOXICOLOGICAL INFORMATION

C.I. Solvent Blue 98:

Oral LD50 (Rat) > 5000mg/kg

C.I. Solvent Red 164:

No Data

Xylene:

Oral LD50 (Rat): 4300 mg/kg

Inhalation LC50 (Rat): 5000 PPM/4-hours

Ethyl Benzene:

Oral LD50 (Rat): 3500 mg/kg

Dermal LD50 (Rabbit): 17800 mg/kg

Silver:

The Registry of Toxic Effects of Chemical Substances (RTECS) reports the following effects in laboratory animals: Tumorigenic - equivocal tumorigenic agent by RTECS criteria.

Mutagenicity:

For C.I. Solvent Blue: Positive results were obtained in the AMES test.

For C.I. Solvent Red: Positive results were obtained in histidine-dependent auxotrophs of salmonella typhimurium.

12. ECOLOGICAL INFORMATION

No Data

13. DISPOSAL CONSIDERATIONS

Waste Management Information:

Dispose of solid waste in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

D.O.T. PROPER SHIPPING NAME: None	HAZARDOUS SUBSTANCE (CERCLA): No
D.O.T. HAZARD CLASSIFICATION: PRIMARY: None	SECONDARY: None
D.O.T. LABELS REQUIRED: None	D.O.T. PLACARDS REQUIRED: None
BILL OF LADING DESCRIPTION: None-hazardous, Wafer Grip Adhesive	UN/NA CODE: N/A

15. REGULATORY INFORMATION

This product contains no materials in quantities considered to be hazardous under Occupational Safety and Health Administrations (OSHA) final standard "Hazardous communications 29CFR1910.1200".

OSHA (USA) hazardous chemicals(s) according to 29CFR1910.1200: none
Materials known to the state of California (USA) to cause cancer and to cause adverse reproductive effects: none

Chemicals subject to the reporting requirement of section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40CFR Part 372 (USA): Xylene, Ethyl Benzene, Silver

CERCLA: Xylene – R.Q. 100 lbs.; Ethyl Benzene – R.Q. 1000 lbs.; Silver – R.Q. 1000 lbs.

SARA (USA) Section 311 and 312 hazard classifications: N/A

All components of this product are listed on the TSCA Inventory or are exempt from TSCA Inventory Requirements.

16. OTHER INFORMATION**CONDUCTIVE WAFER GRIP ADHESIVE FILM**

CAUTION: Do not overheat WG Adhesive.
Recommended application temperature
is 210-225° F.

Although the information and recommendations set forth herein are presented in good faith and believed to be correct, Dynatex International makes no representations as to their completeness or accuracy. Information is supplied upon the condition that the persons receiving will make their own verification and determination as to its suitability for their purposes prior to use. In no event will Dynatex International be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information.

NO REPRESENTATION OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR PRODUCT TO WHICH INFORMATION REFERS.

EMERGENCY TELEPHONE NUMBER: (707) 542-4227